

Starting point formulation – Pigment concentrates based on castor oil with BYK-9076

				Pigment	Kronos 2190	Bayferrox 3920	Bayferrox 130 M	COLORTHERM Green GN	Irgalite Blue GL–NF	Special Black 4
				Supplier	Kronos International	Lanxess	Lanxess	BASF	BASF	Orion Engineered Carbons
Position	Component	Supplier	Function	PW 6	PY 42	PR 101	PG 17	PB 15	PBI 7	
1	Castor oil		Solvent	48.20	45.90	45.90	40.50	81.20	87.00	
2	BYK-9076	BYK	Wetting and dispersing	1.50	3.80	3.80	4.20	3.80	3.00	
3	RHEOBYK-7410 ET	BYK	Anti-settling	0.30	0.30	0.30	0.30	-	-	
4	Pigment	See headline	Color	50.00	50.00	50.00	55.00	15.00	10.00	
Total				100.00	100.00	100.00	100.00	100.00	100.00	

Instructions

Premix position 1 and 2, then add RHEOBYK-7410 ET and the pigment while stirring.

The pigment content is based on the selection of the pigment and can vary, when different pigments regarding rheological behavior are chosen.

Characteristic data

Additive dosage (solids on pigment)

BYK-9076	3.00 %	7.50 %	7.50 %	8.40 %	25.00 %	30.00 %
----------	--------	--------	--------	--------	---------	---------

BYK-Chemie GmbH
Abelstraße 45
46483 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK-DYNWET®, BYK-MAX®, BYK-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKJET®, BYKOZBLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAC®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISITE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBLEND®, RECYCLOBYK®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SCONA®, SILBYK®, TIXOGEL® and VISCOBYK® are registered trademarks of the BYK group.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions.

