

Starting point formulation – Tire shine – Sprayable surfactant-free pickering emulsion

Provides an hydrophobic effect and high gloss on the tire – utilizing BYK-1797 and LAPONITE-RD

Formulation

Position	Component	Supplier	Function	Weight (g)
1	Demineralized water		Solvent	79.05
2	Sodium chloride (NaCl)	Multiple	Electrolyte	0.05
3	LAPONITE-RD (100%)	ВҮК	Emulsifier	0.90
4	BYK-1797 (100%)	ВҮК	Surface protection and gloss	20.00
Total				100.00

Instructions


- Mix water and sodium chloride with a homogenizer at 1500 rpm.
- Weigh the perfume oil and the LAPONITE-EP into seperate containers.

Turn off the homogenizer and carry out each of the following steps in immediate succession:

- Add the BYK-1797 and the LAPONITE-RD.
- Stir the mixture for 10 min at 10,000 rpm.

Allow the formulation to cool and fill in the desired spray bottle.

The formulation is a white and low viscous fluid and develops a very soft thixotropic behavior within a few hours.



O BYK

Characteristic data/specification

Data	Unit	Value
LAPONITE content	%	0.90
Silicone content	%	20.00
Ratio BYK-1797 : LAPONITE		100.00 : 4.50

Further information/application

• The tire shine emulsion is designed to be used as it is.

• Spray a thin layer of the formulation on the tire wall. After drying, the products form a transparent, glossy and water-repellent coating.



ADD-MAX®, ADD-VANCE®, ANTI-TERRA®, AQUACER®, AQUAMAT®, AQUATIX®, BENTOLITE®, BYK®, BYK-AQUAGEL®, BYK®-DYNWET®, BYK-MAX®, BYK®-SILCLEAN®, BYKANOL®, BYKCARE®, BYKETOL®, BYKIET®, BYKO2BLOCK®, BYKONITE®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, CLAYTONE®, CLOISTE®, DISPERBYK®, DISPERPLAST®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, HORDAMER®, LACTIMON®, LAPONITE®, MINERPOL®, NANOBYK®, OPTIBENT®, OPTIFLO®, OPTIGEL®, POLYAD®, PRIEX®, PURABYK®, PURE THIX®, RECYCLOBLEND®, RECYCLOSSORB®, RECYCLOSTAB®, RHEOBYK®, RHEOCIN®, RHEOTIX®, SICDNA®, SILBYK®, TIXOGEL® and VISCOBYK® **are registered trademarks of the BYK group**.



BYK-Chemie GmbH Abelstraße 45 46483 Wesel Germany Tel +49 281 670-0 Fax +49 281 65735

This issue replaces all previous versions.

info@byk.com www.byk.com The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products metioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

HC-SF 30 09/2023

A member of 🜔 ALTANA